

Garantisadong
**NO MORE
LEAKS**TM

AFFORDABLE pa!



MONDO® PLEXI-TITE™ is a water-based acrylic polymer formulated to be blended with portland or pozzoland cement. The resulting polymer-cement compound, when applied properly, results in a tough but flexible membrane capable to bridge hairline cracks. It possesses excellent water-proofing barrier for concrete surfaces, with superior adhesion, mechanical and flexibility properties.

MONDO® PLEXI-TITE™ ay isang water-based acrylic polymer na may katangi-tanging formulation upang maiging humalo sa ano mang uri ng semento (portland o pozzolan). Ang pinaghalong polymer at semento kapag naipahid nang maayos ay magbibigay ng matibay pero flexible film coating na may mahusay at kakayahang mag bridge ng hairline cracks. Ito rin ay may mainam na water-proofing barrier para sa konkretong pader o sahig na nagbibigay ng napakatibay na kapit, na may mechanical at flexibility na katangian.

HOW TO USE

1. Surface Preparation

The surface should be clean and dry, free from oil, grease, dust, dirt, loose materials and other contaminants.

Paghahanda ng Surface o A-applyang Konkreto

Bago mag-apply ng **MONDO® PLEXI-TITE™** siguraduhing malinis na malinis ang a-applyan. Walang alikabok, bahid ng langis o grasa, dumi, tilamsik ng semento o bukol sa rebokada.

2. Mixing Procedure

Add cement gradually to **MONDO® PLEXI-TITE™** and continue mixing for 3-5 minutes until the desired consistency is obtained.

**Note: Don't Add Water*

Preparasyon ng Paghalo

Habang hinahalo ang **MONDO® PLEXI-TITE™** dahan-dahang idagdag o isama ang semento at patuloy ang paghalo hanggang 3-5 na minuto hanggang makuha ang nais na halo ng **MONDO® PLEXI-TITE™** at semento. (tignan ang table ng Mixing Ratio)

**Tandaan: Bawal Haluan ng tubig*

3. Application

a. Wet masonry surfaces thoroughly with water.

b. Apply **MONDO® PLEXI-TITE™** cement mixture using brush or roller. For best results let applied **MONDO® PLEXI-TITE™** cure for 3 days before applying desired painting system.

Ang Pag Apply

a. Basain ng tubig ang mukha ng a-applyan ng **MONDO® PLEXI-TITE™** mixture.

b. I-apply ang **MONDO® PLEXI-TITE™** cement mixture gamit ang brush o roller. Para sa mas mainam at matibay na pamimintura, patuyuin ng maigi ang inapply na **MONDO® PLEXI-TITE™** ng 3 araw bago mag-pahid ng ninanais na painting system.

MIXING RATIO:

Substrate	MONDO PLEXI-TITE™	Cement	No. of Coats	Practical Coverage
Vertical (firewalls, exterior walls, planters, basement)	4 Liters	+ 6 Kilos	3 (brush) 2 (roller)	10-12 m ²
Horizontal (roof decks, balconies, ledges, bathrooms)	4 Liters	+ 6 Kilos	4-5 (brush) 3-4 (roller)	5-6 m ²

** Workability : 30-45 minutes*

** Pot Life : 2 Hours*

Properties:

Type : Acrylic Modified

Color : Milky White

Density : 1.00-1.06 k/l

Pack Size : 4 Liter

Shelf Life : One year when stored in dry & cool conditions

Clean up : When all equipments with clean water

Note: Coverage per package is dependent on the porosity and roughness of substrate.

MAIN FEATURES



Waterbased

low odor, non-toxic and environment friendly

ito ay hindi masakit sa ilong, hindi nakakalason, mabait sa kapaligiran



Durable

has an excellent UV exposure resistance that prolong the service life of the structure

May mataas na UV resistance na nag papatibay para sa pang-matagalang gamit



Affordable

superb quality with a reasonable price


matibay na kalidad sa murang halaga



Excellent Adhesion

provides superior bond strength to concrete, metal, wood, bricks and insulation foams


nagbibigay ito ng matinding bond strength sa konkreto, bakal, kahoy, bricks at insulation foam



Water Resistant

resists water seepage; suitable for positive water pressure on exterior and interior vertical walls

mainam na panangga sa tumatagas na tubig, angkop para sa positive pressure sa loob at labas ng pader



Flexible

greatly reduces concrete chipping even for thin mortar finishes

ito ay nagbibigay ng magandang crack bridging properties upang hindi madaling mag-chipping o pumilas ang konkreto kahit na sa manipis na palitada

WHERE TO USE

• ROOF DECK • BATHROOM • FIREWALL • BALCONY • BASEMENT • PLANTERS • GUTTERS

Davies Paints Philippines, Inc.

1415 A. Sandoval Ave., cor. Mercedes Ave., San Miguel, Pasig City 1600, Philippines



(02) 8570-7000
Customer Care Hotline



www.daviespaints.com.ph



<https://www.facebook.com/DaviesPaintsPhilippines>



<http://instagram.com/daviespaints>