

# MONDO™

WORLD-CLASS BUILDING SOLUTIONS

**BRIDGING GAPS  
MADE EASY**





For Gypsum Board  
Fiber Cement Board



For Ceiling, Gaps  
and Joints



**STEP 1: Surface Preparation**  
Ensure surface is dry & clean structurally sound and free of dust, oil, laitances, paint curing agent, algae and mildew.



**STEP 2: Product Preparation**  
Mix **MONDO™ JC-10™ Premium Joint Compound** with clean tap water with the ratio of 2 kgs **MONDO™ JC-10™ Premium Joint Compound** to 1 liter water.



\*do not add water to extend workability

- STEP 3: Application**
1. Apply with several light strokes using stainless steel trowel or putty knife to cover fill any gaps in joint and edges.
  2. Allow each coat to dry completely to build up thickness.
  3. A mesh or paper tape maybe used to reinforce the joints or cracks before applying **MONDO™ JC-10™ Premium Joint Compound**.
  4. Sand the joint compound to smoothen the applied area.
  5. Apply the recommend Coating System.



**MONDO™ JC-10™ Premium Joint Compound** is a multi-purpose mineral-based powder joint filler used in all phases of finishing including filling, patching, and taping to create a seamless, even and smooth surface. **MONDO™ JC-10™ Premium Joint Compound** is a suitable for a wide range of interior materials such as concrete, wood, gypsum, fiber cement board.

**PRODUCT SPECIFICATION**

• **MIXING RATIO** (by weight)  
MONDO™ JC-10 + 1 Liter water

• **COVERAGE**

65 sqm / Coat / 20kg Bag (based on 3 coats application as Joint Filler)

• **RECOAT**

60 Minutes

• **WORKABILITY**

30 Minutes

• **SHELF LIFE**

9 MONTHS

9 Months when stored in dry and cool conditions (when stored correctly)

• **STORAGE**

Store in a cool, dry place to prevent premature curing due to moisture.

**Davies Paints Philippines, Inc.**

1415 A. Sandoval Ave., cor. Mercedes Ave., San Miguel, Pasig City 1600, Philippines