

STOPS LEAKS FAST!

ROOFS

GUTTERS



FIREWALLS

NAILHEADS

MONDO™ LIQUID SEAL™ is a high quality water-based elastic sealant and waterproofing membrane for multi-substrates. It is a versatile gap filler and sealer to stop water leakages and moisture ingress in roofs and gutters, PVC Pipes, Metal Sheets and other construction materials such as concrete and wood. As a waterproofing membrane, it dries to a strong, durable and flexible bond to provide a long-lasting air-water resistive barrier.

FEATURES & BENEFITS

- Ready to use. Easy to apply, fast drying
- Adheres perfectly to most non-porous substrates
- Superior Flexibility and crack-bridging ability
- Outstanding water-resisting property
- Non-corrosive on metal surfaces
- Non-sag for vertical use
- Paintable with water-based paint systems
- Water-based, non-toxic & environment friendly

Roof, Walls & Deck Waterproofer

Application

1. Surface Preparation
To ensure optimum adhesion, substrates must be sound, clean, dry, and free from loosely-adhering material.
2. Dilute 4L **MONDO™ LIQUID SEAL™** with 1/2L of water.
3. Apply using brush or roller.
4. Apply first coat, let dry for 2 to 3 hours before subsequent coat of **MONDO™ LIQUID SEAL™**. For severe cracks on walls that are non-structural, you may use Waterproofing Fiber Glass Mesh immediately after the first coat while it is wet. Dab the fiber mesh with brush onto wet sealant. Let dry then apply second coat.

Mixing Guide: 4-L **MONDO™ LIQUID SEAL™** + 1/2 -L water
 Coverage: 16-20 sqm / coat
 No. of Coats: Vertical area : 2 coats
 Horizontal area : 3 coats

Elastic Sealant

Application

1. Surface Preparation
To ensure optimum adhesion, substrates must be sound, clean, dry, and free from loosely-adhering material.
2. Apply **MONDO™ LIQUID SEAL™** Using putty knife or trowel. Use as is, do not dilute.

As Elastomeric Waterproofer

| | |
|---|--|
| Recommended Film Thickness: | 300 microns |
| Thinning: | 4L Liquid Seal with 1/2 L clean water |
| Theoretical Spreading Rate per 150 microns: | 16 m ² / 4L / coat |
| No. of coats: | 2 coats |
| Applicator: | Roller or Brush |
| Practical Coverage / 2 coats: | 2 m ² / 1L or 8 m ² / 4L |

Available Sizes:

4L (5.500 Kgs.)
 1L (1.350 Kgs.)
 1/4L (350 gms.)

Where to use



Davies Paints Philippines, Inc.

1415 A. Sandoval Ave., cor. Mercedes Ave., San Miguel, Pasig City 1600, Philippines

