

FLEX-IT™

2-PACK CEMENTITIOUS WATERPROOFING



DAVIES MONDO™ FLEX-IT™ is a two-component cementitious waterproofing system designed to offer a perfect balance of performance features and mechanical properties. **DAVIES MONDO™ FLEX-IT™** It imparts excellent substrate adhesion, high flexibility and elongation capable to bridge fine cracks in interior and exterior applications.

DAVIES MONDO™ FLEX-IT™ supplied in a pre-packaged form with 2.5 liters **Part A** solution and 4.00kg **Part B** cement. When mixed together with a slow-speed drill, the resulting fluid mix can be easily applied guaranteeing outstanding waterproofing properties.

Application Instruction

Surface Preparation

- Surfaces should be clean and dry, free from oil, grease, dust, dirt, loose materials, and other contaminants.
- Surfaces must be flat with no peaks, hollows, and cracks.

SUBSTRATE	No. of Coats (Minimum Required Coating)	Sqm./coat/set	Sqm./set (Based on Required Number of Coating)
VERTICAL (FIREWALL, EXTERIOR WALLS, PLANTERS, BASEMENT)	2	16-20m²	8-10m²
HORIZONTAL (ROOFDECKS, BALCONY, LEDGES, BATHROOM & PARAPETS)	3	12-15 m²	4-5m²

Application

- With constant low-speed mixing, slowly pour Part A 2.50 liter contents into the 4.00 kilo Part B in the pail.
- Mix thoroughly resulting in a homogeneous mixture with no lumps present.



APPLICATION

Paint Brush
Paint Roller



POT LIFE

2 hours @ 28°-30°C

FULL CURE

24 hours



DRYING TIME

Dry to touch
4-5 Hours

Workability
30-45 minutes


Product Features

Flexible cementitious waterproofer suitable for:

- Bathrooms & toilet
- Kitchen areas
- Plant boxes
- Water tanks
- Basement / Terrace / Balcony
- Roof gutters / Retaining walls
- Swimming pools
- Fish ponds

Davies Paints Philippines, Inc.

1415 A. Sandoval Ave., cor. Mercedes Ave., San Miguel, Pasig City 1600, Philippines



<https://www.facebook.com/DaviesPaintsPhilippines>



<http://instagram.com/daviespaints>